

FTTS-P-8 Data Sheet

AS9100C and ISO 9001:2008 Certified

Flight Termination Test Set – 8 Tone

35 Hill Ave Fort Walton Beach FL 32548 | PH: 1-888-325-9422 | Fax: 1-850-243-1378 | www.gomicrosystems.com



Features

- Portable
- 8 Tones (1 8 standard)
- IRIG 313-01 Compliant
- Variable RF Output Level
- Variable Carrier Frequency
- 20 Tone model also available
- Antenna and Coaxial Cable included

Applications

- Range Safety
- Test

Description

The Micro Systems, Inc. Model FTTS-P-8 Flight Termination Test Set (FTTS) is a portable unit used for flight-line checkout of flight termination receivers and/or command receiver/decoders.

The FTTS accepts AC power and generates a modulated RF output suitable for interrogation of flight termination receivers and/or command receiver/decoders.

The FTTS can transmit up to 6 tones simultaneously and the RF output power is adjustable from 0 to -127 dBm. The IRIG tones can be switched ON/OFF independently from the control panel.

A 20 Tone version of the FTTS is also available

Technical Specifications

AS9100C and ISO 9001:2008 Certified

Specifications

Size: 9.00" H x 12" W x 5" D (Standard EIA 19" Rack Mount)

Weight: approximately 10 pounds

Power Input: Universal Input: 115 VAC to 230 VAC, 50 to 60 Hz

Carrier Frequency:
 405 to 450 MHz in 100 kHz steps

Carrier Frequency Stability: ±.0005%
 Power Output: 0 to -127 dBm
 Output Impedance: 50 ohms

• Output Connection: Type N Female

• **Modulation:** Wideband FM, ±30 kHz per tone

• Tone Frequencies: Any combination of up to 8 tones per IRIG 313-01

(maximum of 6 tones ON simultaneously)

Remote Control:
 RS-232 (other options available)

Spurious Outputs: -50 dBcHarmonic Distribution: < 2%

Options

- Rackmount
- Select any 8 of 20 available Tones
- 20 Tone model available (FTTS-P-20)
- Local/Remote: RS-232, GPIB, or 10Base100 Ethernet
- Customizable to fit your needs



20 Tone Model (FTTS-P-20)



Ready for Transport

Contact us for custom modifications

For additional information contact:

Micro Systems, Inc. 35 Hill Ave

Fort Walton Beach, FL 32547 PH: 1-888-325-9422

FAX: 1-850-243-1378 www.gomicrosystems.com



a KRATOS company

© 2010 Micro Systems, Inc Specifications subject to change without notice